

ATCOM™

Mineral Insulated Cables

ATCOM (Advanced Thermal Control & Optimization) mineral insulated heating cables are available for use up to 600V and are tested and approved for both hazardous and non-hazardous areas. The cables are factory assembled and tested, ensuring the highest quality product. Since the units consist of a series resistance, virtually any wattage/voltage/length configuration can be produced within the cable's physical operating limits.

The cables are constructed from a single or dual resistive conductor embedded in a mineral insulating powder and covered by an Alloy 825 metallic sheath. The conductor is typically copper, copper nickel alloys, or nichrome alloys.

The powder insulant is magnesium oxide (MgO), an inert powder that provides excellent insulation characteristics at high temperatures – unaffected by temperatures over 2,550 degrees Fahrenheit.




Technical Specs

Rated Voltage	300 & 600 VAC
Max. Maintenance Temp.	1022 F
Max. Continuous Exposure Temp.	1238 F
Power Off Exposure Temp.	1100 F
Min. Bend Radius	6 x diameter
Max. Watts/ft Loading	1-Core, 600V = 65 W/ft 2-Core, 300V = 61 W/ft 2-Core, 600V = 83 W/ft




Design Types


Design B (shown below) is a single-core type with two cold-leads, one for each end.



Design D (shown below) is a dual-core type with one cold-lead on the end, and an end-cap on the other.



Model Number Format



The model shown above is: Design D, Rated 300V, 2-Core, Alloy 825, 0.2 Ohm/ft, 200', 1210W, 220V, 7' Cold-lead.

› Designed and assembled in the USA

BrandSafway provides access and industrial service solutions with turnkey installation, engineering support and safety training.

› Ready to Deliver

- | | | | | |
|--------------------------------------|---|---|--|---------------------------------------|
| +Safety
First and Foremost | +Expertise
Industry-Leading Depth/Range | +Solutions
The Broadest Portfolio | +Productivity
Increased at Every Level | +Local
Management and Labor |
|--------------------------------------|---|---|--|---------------------------------------|

Contact us today at
Brand Industrial Services, Inc.
600 Galleria Parkway SE, Suite 1100
Atlanta, GA USA 30339
Toll free: 800 558 4772

Diamond
THERMAL SYSTEMS™
BY BRAND SAFWAY

BRAND SAFWAY®

For more information, visit www.brandsafway.com